

# Mercasol 845 D

## Fast drying underbody protection

### General

Mercasol 845 D is a rust preventing product consisting of bitumen, rust inhibitors and solvents. The product is unique as it is the fastest drying material in the Mercasol product range. This product will approx. dry after 1 h at 23° C with good air circulation.

### Application areas

Mercasol 845 D is used on the underbody of vehicle and offers preventive rust protection and reliable abrasion protection.

### Instructions for use

Surfaces which are meant to be treated shall be dry and free of rust, dirt, salt and oil or similar. Application is recommended to take place indoors at temperatures between 15 – 25° C. Mercasol 845 D is intended to apply with a airless high-pressure pump 1:26 > with a feeding pressure of 4 to 6 bar.

### Package

42301761 / 208-lit fat

### Technical data

Color:	Black
Texture:	Fluid
Type of film:	Solid after drying
Density:	990 ± 20 kg /m <sup>3</sup>
Dry content:	57 ± 3 %
Solvent:	White spirit
Film thickness:	150-350 um wet layer
Flash point:	~+30°C
To be clean with:	White spirit or Renox Milieu
Drying time:	Approx. 1 hour depending air exchange rate, humidity and temp.
Application temperature:	15 - 35° C
Storing time:	12 months
Storing temperature:	5 – 35° C

**For further information we recommend the safety data sheet or instruction on package**

Issue: 2015-02-25



Auson AB, Kungsbacka, Sweden  
T: +46 (0)300-56 20 00  
www.auson.se

These directions and information are intended to guide users during product usage and given without obligation. If in doubt we advise own testing or written advise from us.

