

# Mercasol Transparent ML

## Transparent corrosion protective wax

### General

Mercasol Transparent ML is a solvent borne, well penetrative rust protective material. The product is based on wax, sulfonate and oil and has very beneficial long-term anti corrosion attributes. It is approved accordingly with SS 18 65 11. Mercasol Transparent ML has lower contents of solvents compared to similar products. The product is partly drying oxidative.

### Range of application

Mercasol Transparent ML is intended for usage of professional anti corrosion treatment of cavity, joints etc. on vehicles. The material is suitable for visible spaces where a less conspicuous anti corrosion protection or a material with less solvent is wanted.

The product could also be applied in thin layers as a primer for open surfaces before application of underbody coating for vehicles. We recommend using **Mercasol 845** or **Mercasol 845AL**.

### Instructions for use

Surfaces to be treated should be cleaned and free from dirt, salt and oil. We recommend application to take place indoors. Mercasol Transparent ML is primarily intended to apply with an airless high pressure pump 1:26 > with a feeding pressure of 3 to 5 bar. The product can also be applied with a low pressure pump 1:3 air assisted. At application with air distribution cleaning of spray gun is recommended when changing barrel.

### Package

42600701 / 60-lit barrel  
42600721 / 208-lit barrel

### Technical data

Color:	Transparent
Consistency:	Liquid
Type of film:	Vaxy
Density at 20° C:	870 ± 20 kg / m <sup>3</sup>
Dry content:	70 ± 3 %
Solvents:	Aliphatic naphta
Film thickness:	150 µm wet layer gives 90 µm dry layers. When priming on car body should a maximum wet layer of 70 µm be applied.
Removal with:	Aliphatic naphta
Application temperature:	15 - 35° C
Material pressure:	0, 15 lit/ m <sup>2</sup> .
Storing time:	12 months
Storing temperature:	5 - 35° C

**For further information we recommend the safety data sheet or instruction on package.**

Issue: 2015-01-14



Auson AB, Kungsbacka, Sweden  
T: +46 (0)300-56 20 00  
www.auson.se

Dessa anvisningar och information är avsedda att vägleda förbrukaren vid användning av produkten och lämnas utan förbindelse. Vid oklarhet tillråds egna prov eller skriftliga råd från oss.

