

# Noxudol 720



## Waterborne rust preventive product

### General

Noxudol 720 is a thixotropic, waterborne rust preventive product which after drying forms a soft grease similar film. The product is intended for customer with special demands for penetration and is drip free 10 minutes after application.

### Range of application

Noxudol 720 is intended for the treatment of the hollow spaces of motor vehicles but can also be used as a transport- and storage protection.

### Instructions for use

The object must be dry and totally free from oil- and grease remainder. Apply Noxudol 720 by spraying, brushing or dipping. The film must be dry before it will be exposed of wet or degree of frost.

### Package

41700512 / 1-lit  
41700408 / 20-lit can  
41700722 / 208-lit barrel

### Technical data

Color:	Beige
Consistency:	Thixotropic
Type of film:	Fatty
Density at 20° C:	990 ± 20 kg/m <sup>3</sup>
Dry content:	35 ± 3 %
Dry film:	40 - 80µm
Application temperature:	15 - 25° C
Removal with:	Renox Milieu or white spirit
Storing time:	Max 12 months, must not freeze
Storing temperature:	5 - 35° C

**For further information we recommend the safety data sheet or instruction on package**

Issue: 2015-01-13



Auson AB, Kungsbacka, Sweden  
T: +46 (0)300-56 20 00  
www.auson.se

Dessa anvisningar och information är avsedda att vägleda förbrukaren vid användning av produkten och lämnas utan förbindelse. Vid oklarhet tillråds egna prov eller skriftliga råd från oss.

**Noxudol**