

# Chinese Wood Oil

## Wood protection based on Tung oil

### General

**Chinese wood oil** or Tung oil is extracted from the seeds of the Tung tree. Thanks to its extremely small molecules, the oil has excellent depth penetration properties and has long been used to protect wood against moisture penetration and cracking. It is also suitable for treating hardwoods such as teak and mahogany. The oil is combined with linseed oil and solvent.

### Range of application

**Chinese Wood Oil** can be used on Garden furniture, windows, doors and boats etc. It can be used both indoors and outdoors.

Avoid using **Chinese Wood Oil** for hardwood such as larch, oak and/or other similar type of woods.

### Instructions for use

The surface must be dry and clean. Highly absorbent surfaces should be coated until saturated. Any excess oil should be wiped off with a rag.

**NB!** Soaked rags, cotton waste, etc. can self-ignite and so should be soaked in water and discarded in a fireproof location. Do not treat outdoor wood too early in spring, as it is best to allow the sun to dry out the timber.

### Package

20300401 / 1-lit can  
20300473 / 3-lit can

### Technical data

Color:	Light yellow
Density:	0,85 kg/ lit
Dry Content:	45%
Coverage:	4-10 m <sup>2</sup> /lit depending on the dryness of the wood
Drying time:	Approx. 1 day depending on temperature and humidity
Solvents:	Aliphatic naphtha
Cleaning:	Aliphatic naphtha

**For further information we recommend the safety data sheet or instruction on package.**

Issue: 2020-11-25 / AA

