

Cold Asphalt

Moisture barrier on building sites

General

Cold asphalt is an asphalt solution, easy to apply. After drying it forms a moisture resistant and waterproof surface.

Range of application

Cold asphalt is especially suited as a moisture barrier on building sites and concrete surfaces above and below ground. Cold asphalt can also be used as a surface coating on dried out roofing-felt as well as a satisfactory protection on iron and steel structures under ground.

When diluted with 10-20% white spirit, Cold Asphalt can be used for ground coating of dried out ceiling paper.

Instructions for use

Apply Cold Asphalt with spray equipment by dipping or by brushing. If necessary it can be diluted with a smaller amount of white spirit.

Package

10900401 / 1-lit can (4 pieces per pack.)
10900405 / 5-lit can
10900406 / 10-lit can

Technical data

Density:	900 ± 20 kg/m ³
Dry content:	58 ± 5 %
Solvent:	White spirit
Drying time:	6 – 12 h depending on film thickness
Coverage:	0,3 – 0,4 liter / m ²
Cleaning:	White spirit
Drying time:	Approx. 3-4 h (Surface dry at +20°C)

For further information we recommend safety data sheet or instruction on package

Issue: 2023-11-01



Auson AB, Kungsbacka, Sweden
T: +46 (0)300-56 20 00
www.auson.se

These information are for guidance only and are given without obligation. If there is some confusion we recommend that you do your own tests and ask for advice in writing from us.